

Supermicro NVIDIA GB200 NVL72

Liquid-cooled Exascale Compute in a Rack with 72 NVIDIA Blackwell GPUs



Scalable Compute Unit Built For Trillion Parameter Al Models

- 72 NVIDIA Blackwell GPUs: acting as one GPU with a massive pool of HBM3e memory to deliver the most efficient exascale computing in a rack
- **Pioneers in Liquid Cooling**: total liquid-cooling solution with up to 40% reduction in electricity cost for data center
- Unmatched Manufacturing Scale: with the largest liquid cooling rack-level manufacturing capacity, Supermicro ensures timely and high-quality deployment of the GB200 NVL72, supported by production facilities in San Jose, CA, Europe, and Asia
- **Comprehensive Service Offering**: from proof of concept to full-scale deployment, Supermicro is one-stop shop, providing all necessary parts, networking solutions, and on-site installation services
- Advanced Networking Ready: Supermicro is at the forefront of adopting NVIDIA BlueField®-3 SuperNIC, Spectrum™-X, Quantum-2, and next generation 800 Gb/s networking platforms

An Exascale Supercomputer in a Rack

Supermicro accelerates the industry's transition to liquid-cooled data centers with NVIDIA Blackwell to deliver a new paradigm of energy-efficiency for the rapidly heightened energy demand of AI infrastructure. With extensive experience deploying large scale direct-to-chip (DLC) liquid-cooled AI systems, Supermicro's leading liquid-cooling technology advancement powers NVIDIA GB200 NVL72, an exascale computing in a single rack, providing up to 25 times more energy efficiency than the previous generation.

Powered by Supermicro End-to-End Liquidcooling Solution

Supermicro NVIDIA GB200 NVL72 SuperCluster features the new advanced in-rack or in-row cooling distribution unit (CDU) and custom coldplates designed for the compute trays housing the NVIDIA GB200 Grace[™] Blackwell Superchips. The NVIDIA GB200 NVL72 delivers exascale computing capabilities in a single rack with fully integrated liquid-cooling. It incorporates 72 NVIDIA Blackwell GPUs and 36 Grace CPUs interconnected by NVIDIA's largest NVLink[™] network to date. The NVLink Switch System facilitates 130 terabytes per second (TB/s) of total GPU communications with low latency, enhancing performance for AI and high-performance computing (HPC) workloads.

End-to-End Onsite Deployment Services

From proof-of-concept (PoC) to full-scale deployment, Supermicro is a one-stop shop, providing all necessary parts, Liquid-Cooling, networking solutions, management software, and onsite installation services. As a one-stop shop, Supermicro delivers a comprehensive, in-house Liquid-Cooling ecosystem, encompassing custom-designed cold plates optimized for various GPUs, CPUs and memory modules, along with multiple coolant distiribution unit form factors and capacity, manifolds, hoses, connectors, cooling towers, and monitoring and management software. This end-to-end solution seamlessly integrates into rack-level configurations, significantly boosting system efficiency, mitigating thermal throttling, and simultaneously reducing both the Total Cost of Ownership (TCO) and environmental impact of data center operations for the era of Al.

Rack Scale Design Close-up



Management Networking

- In-band management switch
- Out-of-band management switch

10 Compute Trays

- 4x NVIDIA Blackwell GPUs per tray
- 2x NVIDIA Grace CPUs per tray

Compute Interconnect

- 9x NVLink Switches
- 72 GPUs and 36 CPUs inteconnected at 1.8TB/s

o 8 Compute Trays

- 4x NVIDIA Blackwell GPUs per tray
- 2x NVIDIA Grace CPUs per tray

Liquid-Cooling Options

- Supermicro 250kW capacity coolant distribution unit (CDU) with redundant PSU and dual hot-swap pumps
- 240kW or 180kW capacity Liquid-toair solution (no facility water rquired)

SuperCloud Composer (SCC) for Liquid-Cooled Data Center Management

Supermicro's comprehensive datacenter management platform, SuperCloud Composer software, provides powerful tools to monitor vital information on liquidcooled systems and racks, coolant distribution units, and cooling towers, including pressure, humidity, pump and valve conditions and more. SuperCloud Composer's Liquid-Cooling Consult Module (LCCM) optimizes the operational cost and manages the integrity of liquid-cooled data centers.



72-GPU Scalable Unit		SRS-GB200-NVL72-M1
GPUs	72x NVIDIA Blackwell B200 GPUs	
CPUs	36x NVIDIA 72-core Grace Arm Neoverse V2	
Compute Trays	18x 1U ARS-121GL-NB0	
NVLink Switch Trays	9x NVLink Switch, 4-ports per compute tray connecting 72 GPUs to provide 1.8TB/s GPU-to-GPU interconnect	
Power Shelves	8x 1U 33kW (6x 5.5kW PSUs), total power 132kW	
Rack Dimensions (mm)	W 600 x D 1068 x H 2236	
Liquid Cooing Options	 1x in-rack Supermicro 250kW capacity CDU with redundant PSU and dual hot-swap pumps 1.3MW capacity in-row CDU 180kW/240kW capacity liquid-to-air solutions for facilities without cooling tower and water supply 	

Compute Tray		ARS-121GL-NBO	
Overview	1U Liquid-cooled System with 2x NVIDIA GB200 Grace Blackwell Superchips		
CPU and GPU	 2x 72-core NVIDIA Grace Arm Neoverse V2 CPU 4x NVIDIA Blackwell B200 per Superchip 		
GPU Memory	Up to 384GB HBM3e per Superchip (768GB per tray)		
CPU Memory	Up to 480GB LPDDR5X per Superchip (960GB per tray)		
Networking	4x NVIDIA NVLink Switch ports		
Storage	8x E1.S PCle 5.0 dri	ves	
Power Supply	Shared power thro	ugh 4+4 rack power shelves	
A 11 12 1			

Subject to change

Subject to change

© 2024 Copyright Super Micro Computer, Inc. Specifications subject to change without notice. All other brands and names are the property of their respective owners. All logos, brand names, campaign statements and product images contained herein are copyrighted and may not be reprinted and/or reproduced, in whole or in part, without express written permission by Supermicro Corporate Marketing.