

MP SuperServer SYS-442B-NR

4U 4-socket system with 64 DIMMs and 24 NVMe/SAS/SATA drive bays



Key Applications



Business Intelligence, ERP, CRM, Scientific Virtualization, In-Memory Database, HCI, SAP HANA,

Key Features

- Quad E2 (LGA-4710) Intel® Xeon® 6700 series processors with P-cores (4S/8S) up to 350W with air cooling;
- Support for up to 6 double-width GPU accelerator cards;
- Up to 64 DIMMs supporting up to 8TB DDR5 in 2DPC;
- Flexible networking with up to 2 OCP 3.0 compatible AIOM slots;
- Up to 4 PCIe 5.0 x8 FHHL + 2 PCIe 5.0 x16 FHHL + 8 PCIe 5.0 x8 FHFL + 4 PCIe 5.0 x16 FHFL + 2 PCIe 5.0 x16 AIOM;
- Up to 24 front hot-swap 2.5" NVMe/SATA/SAS drive bays;
- 4 Redundant 2700W Titanium Level Hot-plug power supplies;



Form Factor	4U Rackmount Enclosure: 438.4 x 177 x 848.7mm (17.3" x 7" x 33.4") Package: 694 x 405 x 1255mm (27.32" x 15.94" x 49.41")
Processor	Quad E2 (LGA-4710) Intel® Xeon® 6700 series processors with P-cores (4S/8S) Up to 86C/172T; Up to 336MB Cache per CPU
GPU	Max GPU Count: Up to 6 double-width GPUs CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: PCIe
System Memory	Slot Count: 64 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM Max Memory (2DPC): Up to 8TB 5200MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 24 bays <ul style="list-style-type: none"> • 24 front hot-swap 2.5" PCIe 5.0 NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables) M.2: 1 M.2 PCIe 4.0 x4 NVMe slot (M-key 2280; VROC required for RAID) 1 M.2 PCIe 4.0 x4 NVMe slot (M-key 2280/22110; VROC required for RAID)
Expansion Slots	Default <ul style="list-style-type: none"> • 4 PCIe 5.0 x8 FHHL slots • 2 PCIe 5.0 x16 FHHL slots • 8 PCIe 5.0 x8 FHFL slots • 4 PCIe 5.0 x16 FHFL slots • 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible) Option A* <ul style="list-style-type: none"> • 6 PCIe 5.0 x16 FHFL double-width slots • 2 PCIe 5.0 x16 FHHL slots • 4 PCIe 5.0 x8 FHHL slots • 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
On-Board Devices	Chipset: System on Chip Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 ports(rear) Video: 1 VGA port(Front) 1 DisplayPort port(Rear) Serial: 1 COM port(Rear)



System Cooling	Fans: 10 Heavy duty counter-rotating 8cm Fan(s) Air Shroud: 4 Air Shrouds
Power Supply	4x 2700W Redundant (3 + 1) Titanium Level (96%) Hot-plug power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 7 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 158.9 lbs (72.1 kg) Net Weight: 120.4 lbs (54.6 kg) Available Color: No Paint
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super X14QBH+
Chassis	CSE-418H2TS-R5K4AWP