

UP Workstation SYS-540A-TR

UP full-tower workstation for AI/DL/ML development



More details here

Key Applications

Deep Learning/AI/Machine Learning Development,

Key Features

- Supports 3rd Gen Intel® Xeon® Scalable or Xeon® W-3300 Processors with TDP up to 270W;
- 7 PCIe 4.0 Slots;
- 1x 10GBase-T, 1x 1GbE, and 1x dedicated IPMI LAN ports;



Form Factor	<p>Full-Tower Rackmount</p> <p>Enclosure: 178 x 460 x 673mm (7" x 18.1" x 26.5")</p> <p>Package: 685.8 x 322.6 x 952.5mm (27" x 12.7" x 37.5")</p>
Processor	<p>Single Socket P+ (LGA-4189)</p> <p>3rd Gen Intel® Xeon® Scalable processors</p> <p>Up to 40C/80T; Up to 60MB Cache</p>
GPU	<p>Max GPU Count: Up to 4 double-width or 4 single-width GPU(s)</p> <p>Supported GPU: NVIDIA PCIe: RTX A6000, RTX A5000, RTX A4000</p>
System Memory	<p>Slot Count: 16 DIMM slots</p> <p>Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM/LRDIMM</p>
Drive Bays Configuration	<p>Default: Total 8 bay(s)</p> <ul style="list-style-type: none"> • 8 front hot-swap 3.5" SATA drive bay(s) <p>M.2: 4 M.2 PCIe 4.0 x4 NVMe slot(s) (M-key 2280/22110)</p> <p>Peripheral Bays: 3 5.25" bay(s)</p>
Expansion Slots	<p>Default</p> <ul style="list-style-type: none"> • 7 PCIe 4.0 x16 FHFL slot(s)
On-Board Devices	<p>SATA: SATA (6Gbps)</p> <p>Chipset: Intel® C621A</p> <p>Network Connectivity: 1 RJ45 1GbE with Intel® I210-AT</p> <p>1 RJ45 1GbE with Realtek RTL8211F PHY (dedicated IPMI)</p> <p>1 RJ45 10GbE with Marvell® AQC113</p>
Input / Output	<p>USB: 2 USB 2.0 port(s) (header)</p> <p>2 USB 2.0 port(s) (rear)</p> <p>2 port(s) (header)</p> <p>4 port(s) (rear)</p> <p>Video: 1 VGA port(s)</p> <p>TPM: 1 TPM header</p>



System Cooling	Fans: 4x 92mm Fan(s) 2x 80mm Fan(s)
Power Supply	1x 2200W Redundant Titanium Level (96%) power supply
System BIOS	BIOS Type: AMI 256MB SPI Flash
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	Voltage: +1.8V, +12V, +3.3V, +5V, +5V standby, 10 -fan status, 3.3V standby, HT, Memory, VBAT
Dimensions and Weight	Weight: Gross Weight: 57 lbs (25.85 kg) Net Weight: 52.9 lbs (24 kg) Available Color: black
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<u>Super X12SPA-TF</u>
Chassis	CSE-747BTS-R2K20BP