

Hyper A+ Server AS -2025HS-TNR

2U Hyper with 12 hot-swap 3.5" NVMe/SAS/SATA bays and up to 4 PCIe 5.0 x16 slots



More details here

Key Applications

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server,

Key Features

- Dual AMD EPYC™ 9004/9005* Series Processors
(*AMD EPYC™ 9005 series drop-in support requires board revision 2.x);
- Support up to DDR5 24 DIMM slots (1DPC);
- Optional PCIe slot configurations up to 8 PCIe 5.0 x8 or 4 PCIe 5.0 x16 slots or mix and match
Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible);
- 12 Hot-swap 3.5"/2.5" NVMe/SATA/SAS drive bays
2 M.2 PCIe 3.0 NVMe slots;
- 1600W Redundant Power Supplies (Titanium Level);



Form Factor	2U Rackmount Enclosure: 437 x 88.9 x 803mm (17.2" x 3.5" x 31.6") Package: 605 x 263 x 1107mm (23.8" x 10.4" x 43.6")
Processor	Dual processor(s) AMD EPYC™ 9004/9005 Series Processors (* AMD EPYC™ 9005 Series drop-in support requires board revision 2.x) Up to 320C/640T
GPU	Max GPU Count: Up to 2 double-width or 2 single-width GPUs Supported GPU: NVIDIA PCIe: H100, H100 NVL, A16, A30, A40, L4, L40S, RTX 4000, RTX 6000 Ada Generation, A100, RTX A4000, RTX A4500, RTX A5000, RTX A6000, T1000, RTX A5500, L40, RTX A2000 CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: PCIe
System Memory	Slot Count: 24 DIMM slots Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor) Max Memory (1DPC): Up to 9TB 6000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)
Drive Bays Configuration	Default: Total 12 bays <ul style="list-style-type: none"> • 12 front hot-swap 3.5"/2.5" NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables) M.2: 2 M.2 PCIe 3.0 x4 NVMe slots (M-key 2280/22110)
Expansion Slots	Default <ul style="list-style-type: none"> • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option A* <ul style="list-style-type: none"> • 1 PCIe 5.0 x16 (in x16) FHFL double-width slot • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option B* <ul style="list-style-type: none"> • 2 PCIe 5.0 x8 (in x16) FHFL slots • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option C* <ul style="list-style-type: none"> • 2 PCIe 5.0 x16 (in x16) FHFL double-width slots • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option D* <ul style="list-style-type: none"> • 1 PCIe 5.0 x16 (in x16) FHFL double-width slot • 2 PCIe 5.0 x8 (in x16) FHFL slots • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option E* <ul style="list-style-type: none"> • 4 PCIe 5.0 x8 (in x16) FHFL slots • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) Option F*

- 4 PCIe 5.0 x16 (in x16) FHFL double-width slots
- 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)

Option G*

- 3 PCIe 5.0 x16 (in x16) FHFL double-width slots
- 2 PCIe 5.0 x8 (in x16) FHFL slots
- 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)

Option H*

- 2 PCIe 5.0 x16 (in x16) FHFL double-width slots
- 4 PCIe 5.0 x8 (in x16) FHFL slots
- 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)

Option I*



- 1 PCIe 5.0 x16 (in x16) FHFL double-width slot
- 6 PCIe 5.0 x8 (in x16) FHFL slots
- 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)

On-Board Devices

Chipset: System on Chip
Network Connectivity: Via AIOM

Input / Output

LAN: 1 RJ45 1 GbE Dedicated BMC LAN port
USB: 2 USB 3.0 ports(rear)
Video: 1 VGA port



System Cooling	Fans: 4x 8cm heavy duty fans with optimal fan speed control Air Shroud: 2 Air Shrouds
Power Supply	2x 1600W Redundant Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM BIOS Features: ACPI 6.4 Plug and Play (PnP) SMBIOS 3.5 or later UEFI 2.8 USB Keyboard support
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); OOB Management Package (SFT-OOB-LIC); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors Voltage: System temperature, Memory temperature, CPU temperature, 3.3V standby, +5V standby, +5V, +3.3V, +12V, CPU thermal trip support
Dimensions and Weight	Weight: Gross Weight: 69 lbs (31.3 kg) Net Weight: 39 lbs (17.7 kg) Available Color: Black front & silver body
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	Super H13DSH
Chassis	CSE-HS829-R1K63P-A