

Storage SuperServer SSG-121E-NE316R

1U front-loading all-flash storage server with 16 E3.S NVMe drives and PCIe 5.0



More details here

Key Applications


Software-defined Storage, In-Memory Computing, Data Intensive HPC, Private & Hybrid Cloud, NVMe Over Fabrics Solution,

Key Features

- Dual Socket E (LGA-4677) 5th/4th Generation Intel® Xeon® Scalable processors. Up to 270W TDP.;
- Supports 32 DIMMs with 2DPC, up to 8TB memory capacity with 32 DIMMs of 256GB 3DS RDIMM DDR5-5600 ECC memory;
- Two PCIe 5.0 x16 slots & two AIOM connectors (OCP 3.0 SFF compliant);
- 16x hot-swap E3.S (7.5mm) NVMe drive bays;
- Redundant Titanium 1600W Power Supplies;



Form Factor	1U Rackmount Enclosure: 438.4 x 43.6 x 773.25mm (17.2" x 1.7" x 30.4") Package: 604.774 x 199.898 x 1029.97mm (23.81" x 7.87" x 40.55")
Processor	Dual Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors
System Memory	Slot Count: 32 DIMM slots Max Memory (2DPC): Up to 8TB 5600MT/s ECC DDR5 RDIMM/LRDIMM
Drive Bays Configuration	Default: Total 16 bays • 16 front hot-swap E3.S 1T NVMe drive bays M.2: 2 M.2 NVMe/SATA slots (M-key 2280/22110)
Expansion Slots	Default • 2 PCIe 5.0 x16 FHHL slots • 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
On-Board Devices	Chipset: Intel® C741 Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 ports(rear) 2 USB 3.0 ports(front) Video: 1 VGA port



System Cooling	Fans: 8 Heavy Duty 4cm Fan(s) Air Shroud: 2 Air Shrouds
Power Supply	2x 1600W Redundant Titanium Level (96%) Hot-plug power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 7 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 68.74 lbs (31.2 kg) Net Weight: 48 lbs (21.8 kg) Available Color: Silver
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% () Non-operating Relative Humidity: 8% to 95% ()
Motherboard	Super X13DSF-A
Chassis	CSE-126E32-R1K62P