

# Hyper SuperServer SYS-212HA-TN

2U UP Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and up to 3 PCIe 5.0 + 1 PCIe 5.0 AIOM slots



## Key Applications

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server, Data Center Optimized, Database Processing and High Density Storage,

## Key Features

- Hyper is a flagship performance rackmount server designed for scale-out cloud workloads.;
- Single Intel® Xeon® 6 6900 series Processor.;
- 12 DIMM slots supporting up to 3TB of 8800 MRDIMM;
- Double width add-on card support.;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible).;
- Breeze through high throughput workloads with PCIe 5.0 NVMe drive support.;
- Trusted Platform Module (TPM) 2.0 onboard.;
- Modularized and Tool-less design for easy serviceability.;



<b>Form Factor</b>	2U Rackmount Enclosure: 437 x 88.9 x 806.2mm (17.2" x 3.5" x 31.74") Package: 672 x 253 x 1100mm (26.46" x 9.96" x 43.31")
<b>Processor</b>	Single Socket BR (LGA-7529) Intel® Xeon® 6900 series processors with P-cores Up to 128C/256T; Up to 504MB Cache
<b>System Memory</b>	Slot Count: 12 DIMM slots Max Memory (1DPC): Up to 3TB 8800MT/s ECC DDR5 MRDIMM Max Memory (1DPC): Up to 3TB 6400MT/s ECC DDR5 RDIMM
<b>Drive Bays Configuration</b>	Default: Total 8 bays <ul style="list-style-type: none"> <li>• 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays</li> </ul> Option A: Total 24 bays <ul style="list-style-type: none"> <li>• 24 front hot-swap 2.5" SAS*/SATA* drive bays</li> </ul> (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 2 M.2 NVMe slots (M-key 2280/22110/25110; VROC required for RAID)
<b>Expansion Slots</b>	Option A <ul style="list-style-type: none"> <li>• 1 PCIe 5.0 x16 FH/10.5"L double-width slot</li> <li>• 1 PCIe 5.0 x8 FHFL slot</li> <li>• 1 PCIe 5.0 x16 HHFL double-width slot</li> <li>• 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)</li> </ul> Option B <ul style="list-style-type: none"> <li>• 2 PCIe 5.0 x8 FH/10.5"L slots</li> <li>• 1 PCIe 5.0 x8 FHHL slot</li> <li>• 1 PCIe 5.0 x16 FHFL double-width slot</li> <li>• 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)</li> </ul>
<b>On-Board Devices</b>	NVMe: NVMe; RAID 0/1/5/10 support(Intel® VROC RAID key required) Chipset: System on Chip Network Connectivity: Via AIOM
<b>Input / Output</b>	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.2 Gen1 ports(Rear) Video: 1 VGA port

(Front View – System)



Slot	Description
0 - 7	2.5" Hot-swap NVMe/SAS3/SATA3 Drive Bays*

\*NVMe, SAS3, or SATA3 support requires additional parts from the optional parts list

(Rear View – System)



Slot Description		Slot Description		
Option 1	Option 2	Option 1	Option 2	Option 3
1	Not Available	1	PCIe 5.0 x8 (in x16)†	PCIe 5.0 x8 (in x16)†
2	Not Available	2	Not Available	Not Available
Slot Description		3	PCIe 5.0 x8 (in x16)†	PCIe 5.0 x8 (in x16)†
Option 1	Option 2	4	Not Available	Not Available
1	PCIe 5.0 x8 (in x16)†	2	PCIe 5.0 x8 (in x16)†	PCIe 5.0 x8 (in x16)†
2	Not Available	3	Not Available	Not Available
Slot Description		Slot Description		
1		A1		
Not Available		A2		

†Requires additional parts from the optional parts list

System Cooling	Fans: 6 counter-rotating 60x60x56mm Fan(s)
Power Supply	2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 64MB SPI Flash
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 75 lbs (34 kg) Net Weight: 45 lbs (20.5 kg) Available Color: Silver
Operating Environment	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<a href="#">Super X14SBH-AP</a>
Chassis	<b>CSE-HS201-R000NFP</b>