

# IPMI Firmware / BIOS Release Notes Form

*Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.*

<b>Product Name</b>	<b>H13SSH</b>
<b>Release Version</b>	<b>01.01.03</b>
<b>Release Date</b>	<b>05/26/2023</b>
<b>Previous Version</b>	<b>01.00.36</b>
<b>Update Category</b>	<b>Recommend</b>
<b>Dependencies</b>	<b>N/A</b>
<b>Important Notes</b>	<b>ECO #28273</b> <b>BMC_H13AST2600-ROT20-E401MS_20230526_01.01.03_STDsp.bin</b> <b>BMC_H13AST2600-ROT20-E401MS_20230526_01.01.03_STDsp.zip</b> <b>Please update IPMI with attached Flash Utility in package.</b>
<b>Enhancements</b>	<ol style="list-style-type: none"> <li>1. Retrieve BIOS version from 'OFID'</li> <li>2. KVM launched and closed MEL should display user ID</li> </ol>
<b>New features</b>	<ol style="list-style-type: none"> <li>1. Support BPN-NVME5-HS219N-S24 SATA mode on JRSI2C1</li> <li>2. Auto Daylight Saving Time</li> <li>3. Task Queue &amp; Task List</li> <li>4. Redfish 2020.3 related feature</li> </ol>
<b>Fixes</b>	<ol style="list-style-type: none"> <li>1. Buttons and icons of Virtual Media page can operate while System Lockdown enable</li> <li>2. With HBM CPU, only partial memory modules are listed in IPMI Web GUI memory info</li> <li>3. Fixed BMC GUI sensor arrangement order is not stable.</li> <li>4. Fixed VM mount issue</li> <li>5. Fixed IPMI Lan set ipsrc for dhcp to static IP missing.</li> <li>6. Fixed Unable to close popup window under System lockdown mode</li> <li>7. AD related MEL should not shown when setup LDAP and Radius</li> <li>8. User is able to click delete button on system lockdown mode</li> <li>9. Fixed DMTF/Redfish standard API support test failed</li> <li>10. Webgui crashed after uploading product key with invalid file</li> <li>11. Fail to use SecureErase with SAS 3816 IR card</li> <li>12. IP changed after running raw command</li> <li>13. Network Setting Page Can Now Save With Only 1 Dedicated LAN Speed Capability</li> <li>14. System Lockdown Storage Monitoring Physical View buttons are enabled</li> <li>15. [Redfish] expect length of Service Addresses to be 1 but is actually 3</li> <li>16. change BIOS password fail</li> <li>17. MEL Log msg is incorrect when configure Syslog.</li> <li>18. Fixed chassis intrusion reset button not grey out issue when System Lockdown Mode is on</li> <li>19. AOC-S25G-m2S sensor temp drop</li> </ol>

*Release Notes from Previous Release(s) – these will be appended at the bottom of the current release notes in italic and in smaller print*

**01.00.36 (04/14/2023)**

First release