

# MegaDC SuperServer ARS-210M-NR

2U UP MegaDC supporting up to 4 double-width GPUs + 4 hot-swap 2.5" NVMe drives



More details here

## Key Applications

High Performance Computing, Immersive Media, Cloud Gaming / AICAN, AI Inference / Training, Dense-VDI, Video-on-Demand,

## Key Features

- Single Socket Ampere® Altra® Processor (Up to 80 Cores; Up to 3.3Ghz) / Single Socket Ampere® Altra® Max Processor (Up to 128 Cores; Up to 3.0Ghz) ; Up to 250W TDP;
- 16 DIMMs; Up to 4TB ECC Registered DDR4-3200MHz RDIMM/LRDIMM;
- Supports up to 4 PCIe 4.0 x16 Double Wide GPU Cards (Up to 300W per GPU), 1 PCIe 4.0 x16 LP Slot, 1 AIOM Slot (OCP3.0 Mezzanine Compatible);
- 2x 25Gb LAN SFP28 Ports via Mellanox ConnectX®-4 Lx EN Controller;
- 4x 2.5" U.2 NVMe Hot-Swap Drive Bays (Options available for up to 16 or 24 Drive Bays via a Modular Bay Design);
- 2000W Redundant Titanium Level high-efficiency power supplies;
- 1 VGA, 1 (Serial) Micro USB Port, 2 USB3.0 (2 Rear);



Form Factor	2U Rackmount Enclosure: 437 x 88.9 x 648mm (17.2" x 3.5" x 25.5") Package: 674 x 279.4 x 863.6mm (26.5" x 11" x 34")
Processor	Single FCLGA-4926 Ampere® Altra® / Altra® Max processor
GPU	Max GPU Count: Up to 4 double-width GPUs Supported GPU: NVIDIA PCIe: H100, L40S, L4, A16, A100, A10
System Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM/LRDIMM
Drive Bays Configuration	Default: Total 4 bays <ul style="list-style-type: none"> <li>• 4 front hot-swap 2.5" NVMe drive bays</li> </ul> Option A: Total 16 bays <ul style="list-style-type: none"> <li>• 16 front hot-swap 2.5" SAS*/SATA* drive bays</li> </ul> (*SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 1 M.2 NVMe slot (M-key 22110)
Expansion Slots	Default <ul style="list-style-type: none"> <li>• 4 PCIe 4.0 x16 FHFL slots</li> <li>• 1 PCIe 4.0 x16 LP slot</li> <li>• 1 PCIe 4.0 x16 AIOM slot (OCP 3.0 compatible)</li> </ul>
On-Board Devices	Chipset: System on Chip Network Connectivity: 2 SFP28 25GbE IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 2 SFP28 25 GbE LAN ports 1 RJ45 1 GBASE-T Dedicated BMC LAN port USB: 2 USB 3.0 ports(rear) Video: 1 VGA port Serial: 1 port


(Front View – System)



Slot	Slot Description
1	PCIe 4.0 x16 Dual-Width (GPU)
2	PCIe 4.0 x16 Dual-Width (GPU)

Drive Bay	Description
1 - 4	4 Hot-swap 2.5" NVMe Drive Bays

(Rear View – System)



Slot	Slot Description
1	PCIe 4.0 x16 Dual-Width (GPU)
2	PCIe 4.0 x16 Dual-Width (GPU)
3	PCIe 4.0 x16 LP (occupied by AOC-S3B16, Atrix, x8 only)
4	PCIe 4.0 x16 AIOM (Atrix, x8 only)

**System Cooling**

Fans: 4 Heavy Duty 8cm Fan(s)  
Air Shroud: 1 Air Shroud

**Power Supply**

2x 2000W Redundant (1 + 1) Titanium Level (96%) power supplies

**Management**

KVM with dedicated LAN ; IPMI 2.0

**PC Health Monitoring**

CPU: Monitors for CPU Cores, Chipset Voltages, Memory  
FAN: Fans with tachometer monitoring  
Status monitor for speed control  
Pulse Width Modulated (PWM) fan connectors  
Temperature: Monitoring for CPU and chassis environment  
Thermal Control for fan connectors

**Dimensions and Weight**

Weight: Gross Weight: 59 lbs (26.76 kg)  
Net Weight: 35.3 lbs (16 kg)  
Available Color: Black

**Operating Environment**

RoHS Compliant  
Operating Temperature: 10°C to 35°C (50°F to 95°F)  
Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)  
Operating Relative Humidity: 8% to 90% ( )  
Non-operating Relative Humidity: 5% to 95% ( )

**Motherboard**

[Super R12SPD-A](#)

**Chassis**

CSE-LB26TS-R0AMBNDP